

OEM - 4 post lift according to Mercedes-Benz guidelines

CONSUL[®]



Equipment

Stand 04/2021

- Low noise hydraulic under oil drive
- Electro-hydraulic control
- Separated main switch (can be locked as required by CE)
- Acoustic foot protection
- Hydraulic traction cylinder
- Slack cable and cable failure safety feature and roll back protection
- Integrated rail for jacking beam
- Central control for pneumatic locking device (8 bar)
- Locking bars for overall lifting height with locking device each 100 mm
- Integrated wheel free scissor with extendable support
- Wheel free scissor with Master / Slave hydraulic system
- Protection class IP54, GS approved, DIN EN 1493, CE approved
- Lift in RAL 7015
- Inclusive 40 mm rubber pads
- Inclusive lighting
- Inclusive 1 socket in country-specific design (e.g. 230V/16A)
- Inclusive 2x Y compressed air safety connections
- Inclusive long drive-on ramps (1.500 mm long)
- Inclusive document holder
- Inclusive installation material

| | | |
|--------------------------------------|------------|---------------------|
| Modell | | 4.35 L-SN |
| Article-No. | | 542100 |
| Capacity | kg | 3.500 / 3.500 (SN)* |
| Motor data | kW / A / V | 1 x 3,0 / 16 / 400 |
| Lifting / lowering time | s | 35 |
| A Lifting height | mm | 2.050 |
| B Set-up height | mm | 2.660 |
| C Set-up width ^{1/2} | mm | 3.220 / 6.320 |
| D Drive-on /-over height | mm | 140 |
| E Platform width | mm | 650 |
| F Platform length | mm | 4.800 |
| G Platform width SN* | mm | 650 |
| H Platform length SN* | mm | 1.400 - 1.900 |
| I Lifting height SN* | mm | 450 |
| J Drive-on / -over height SN* | mm | 50 |
| K Clear distance columns | mm | 2.780 |
| L Clear distance platforms | mm | 900 |

SN* = Radfreiheber

